

What is claimed is:

1. A method comprising:

generating a first signal defining 1) a location in a memory, and 2) a length in the memory of a second signal, the first signal having a cross-platform encoding; and storing the first signal such that it may be accessed by an application program.

5

2. The method of claim 1 in which defining the location in the memory comprises defining an offset in the memory.

3. The method of claim 1 in which defining the location in the memory comprises defining an address in the memory.

4. The method of claim 1 in which the cross-platform encoding comprises:

NAME and VALUE fields in an HTML form.

5. The method of claim 1 in which the memory is CMOS and the first signal is stored in RAM.

6. The method of claim 1 in which the second signal comprises a configuration setting.

7. The method of claim 1 in which the application program executes in cooperation with an operating system.

8. A method comprising:

generating a first signal defining 1) a location in a memory, and 2) a length in the memory of a second signal representing a configuration setting for a first computer system, the first signal having a cross-platform encoding; and

5 transmitting the first signal to a second computer system.

9. The method of claim 8 in which the cross-platform encoding comprises:

NAME and VALUE fields in an HTML form.

10. The method of claim 8 further comprising:

storing the first signal such that the first signal is accessible by an application program executing in cooperation with an operating system.

11. A method comprising:

receiving on a first computer system a first signal defining 1) a location in a memory, and 2) a length in the memory of a second signal, the second signal defining a configuration setting for a second computer system, the second computer system

5 comprising the memory, the first signal having a cross-platform encoding; and

the first computer system applying the first signal to read the configuration setting.

12. The method of claim 11 further comprising:

the first computer system altering a value for the configuration setting; and

the first computer system transmitting the value to the second computer system.

13. The method of claim 11 in which the cross-platform encoding comprises:

NAME and VALUE fields in an HTML form.

14. An article comprising:

a machine-readable memory having stored therein instructions which, when executed by a processor in a computer system, result in:

generating a first signal defining 1) a location in a memory, and 2) a length in the  
5 memory of a second signal, the first signal having a cross-platform encoding; and  
storing the first signal such that it may be accessed by an application program.

15. The article of claim 14 in which the cross-platform encoding further comprises:

NAME and VALUE fields in an HTML form.

16. The article of claim 14 in which the memory is CMOS and the first signal is stored in RAM.

17. An article comprising:

a machine-readable memory having stored therein instructions which, when executed by a processor, result in:

generating a first signal defining 1) a location in a memory, and 2) a length in the  
5 memory of a second signal, the second signal defining a configuration setting for a first  
computer system, the first signal having a cross-platform encoding; and  
transmitting the first signal to a second computer system.

18. The article of claim 17 in which the cross-platform encoding comprises:

NAME and VALUE fields in an HTML form.

19. The article of claim 17 in which execution of the instructions further results in:

storing the first signal such that it is accessible by an application program  
executing in cooperation with an operating system.

20. An article comprising:

a machine-readable memory having stored thereon instructions which, when  
executed by a processor, result in;

a first computer system receiving a first signal defining 1) a location in a memory,  
5 and 2) a length in the memory of a second signal, the second signal defining a  
configuration setting for a second computer system, the second computer system  
comprising the memory, the first signal having a cross-platform encoding; and  
transmitting a value of the configuration setting to the second computer system.

21. The article of claim 20 in which the cross-platform encoding comprises:

NAME and VALUE fields in an HTML form.

22. A computer system comprising:

a processor;

a machine-readable medium having stored thereon instructions which, when executed by the processor, result in:

- 5       generating a first signal defining 1) a location in a memory, and 2) a length in the memory of a second signal, the first signal having a cross-platform encoding; and
- storing the first signal such that the first signal may be accessed by an application program.

23. The system of claim 22 in which the cross-platform encoding comprises:

NAME and VALUE fields in an HTML form.

24. The system of claim 22 in which the first memory is CMOS and the first signal is stored in RAM.